

STAIN-PROOF™

PREMIUM IMPREGNATING SEALER **WATERBORNE**

STAIN-PROOF™ Waterborne is a water-based impregnating sealer that provides excellent protection from water and oil based stains on natural stone, tiles, pavers, concrete, brick and grout. Treated indoor and outdoor surfaces become easier to clean and keep looking good for longer.



TYPICAL APPLICATIONS:

STAIN-PROOF™ Waterborne can be used for a wide variety of indoor and outdoor applications in residential and commercial buildings, including: building facades, floors, walls, countertops, showers, swimming pool surrounds, patios, garages, kitchens and entertaining areas.

BENEFITS:

- Short dwell time for quicker application
- Single application
- Premium oil and water repellency for stain protection
- Superior impregnation, breathability, and alkali resistance
- Retains the natural color and finish of the surface.

VOC CONTENT:

US EPA Method 24 < 100g/liter (including water, Low Solid Coating)

PACK SIZE

1 Quart (946 mL)
1 Gallon (3.79 L)

STORAGE:

Keep container tightly sealed in a cool, dry and well ventilated place.

FIRST AID:

FIRST AID: IF SWALLOWED, contact a physician. DO NOT induce vomiting. IF SKIN CONTACT OCCURS, remove contaminated clothing and wash skin thoroughly. IF IRRITATION persists, contact a physician. IF IN EYES, hold open, flood with water for at least 15 minutes and contact a physician. IF BREATHED VAPORS OR MIST, relocate to fresh air. IF SYMPTOMS PERSIST, contact a physician.

COUNTRY OF MANUFACTURE:

Made in USA

HOW TO USE:

1. **TEST PRODUCT ON A SMALL, INCONSPICUOUS AREA FIRST. Allow a 24-hour cure time to determine the ease of application and desired results**
2. Surface must be dry, clean and free of residues.
3. DO NOT thin product.
4. Generously apply STAIN-PROOF™ Waterborne using an applicator pad or foam roller.
5. When touch-dry, apply a second coat before the surface completely dries (Typically about ~10mins) Re-repeat step 4 until surface is adequately sealed. Avoid contact with surrounding areas. Total application rate is approximately one quart per 20 to 250 sq. ft. (one liter per 2 to 25 sqm), depending on surface absorption.
6. After the final coat, wait approximately 30 minutes but before the surface completely dries, wipe the surface thoroughly with clean, dry, white cloths, towels or similar to remove excess product, moistening cloth with STAIN-PROOF™ Waterborne to ease polishing.
7. Use water to clean equipment.
8. **NOTE:** Sealer will **NOT** prevent surface etching, scuff marks or wear and may lighten or darken some surfaces. Spills should be cleaned up immediately to minimize absorption.

PRECAUTIONS:

1. Do not take internally.
2. Apply when surface temperature is between 40 - 95°F (5 - 35°C).
3. Avoid moisture contact with the surface for six hours after application.
4. Protect surrounding areas from sealer.
5. Wear suitable gloves, protective clothing, safety goggles and an mask during application.
6. Wash hands thoroughly after applying
7. Do not smoke during application

WARRANTY:

*A 10-YEAR PERFORMANCE WARRANTY is offered when product applied by an Accredited Applicator following our written instructions and surface is maintained regularly using our written maintenance system, as outlined in our warranty document. Spills should still be cleaned up immediately to minimize absorption.

